

BEN/P SERIES

HOT WATER PRESSURE WASHER

Belt Drive • Electric Powered • NG or LP Heated

- **Upstream Chemical Injector:**
For high pressure soap and chemical injection.
- **Quick Connect Hose Connectors:**
For easy on/off connections and tangle free hoses.
- **Heavy Duty Steel Frame:**
12 gauge steel with powder coated finish.
- **High Pressure Blow-Off Valve:**
For added safety.
- **24 Volt Electronic Ignition:**
Automatically ignites the pilot flame when turned on.
- **High Efficiency Burner:**
Schedule 80 coil with 13,000 burst pressure rating. Ultra hot rated to 350,000 BTU.
- **Belt Drive Motor and Pump Combination.**
Maximizes the life of your pump.
- **Large Burner Temperature Dial:**
Adjust water temperature with ease.
- **Separate Unloader:**
Diverts water pressure when trigger is not in use. Includes easily adjustable pressure control knob and brass fittings.

- **B-Vent Rated:**
This unique design allows the heat stack to be B-Vented. This saves money on installation and venting costs



- **Draft Hood Included**



- **Time Delay Shutdown:**
Automatically shuts down the motor when not in use.
- **Quality Gun and Lance Combination:**
Easy pull trigger with 48" lance.
- **50' High Pressure Hose:**
Durable non-marking steel braided hose.
- **Stainless Steel Coil Skin:**
Durable rust resistant skin.
- **Louvered Guard:**
Allows better circulation, while protecting the belt drives.
- **High Quality Triplex Plunger Pump:**
All Dynablast pressure washers include GP/Interpump pumps with solid ceramic plungers, thermal pump protector and limited 5 year warranty.

Other Features:

- Easy Access On/Off Rotary Switch
- Large Stainless Steel Float Tank
- Hinged Access Panel
- Pressure Gauge
- Baldor Electric ODP Motor
- Flow Switch - For added safety.
- Four Quick Connect Nozzles



ULTRA HOT BURNER

SPECIFICATIONS

ASSEMBLED IN CANADA

MODEL	UHE422BEN/P	UHE430BEN/P	UHE520BEN/P	UHE530BEN/P
Operating Pressure (PSI):	2200	3000	2000	3000
Volume (GPM):	4.0	4.0	5.0	5.0
Motor (HP):	5	7.5	7.5	10
Available Voltage (1 Phase):	230	230	230	230
Available Voltage (3 Phase):	208/230/460/575	208/230/460/575	208/230/460/575	208/230/460/575
Amps:	26/14/13/7/5	32/22/22/11/8	32/22/22/11/8	30/28/14/11
Pump Speed:	1450	1450	1450	1450
BTU:	350,000	350,000	350,000	350,000
Time Delay Shutdown	YES	YES	YES	YES
Unit Dimensions (LxWxH)	47"x23"x41"	47"x23"x41"	47"x23"x41"	47"x23"x41"
Unit Weight	560 lbs	580 lbs	580 lbs	600 lbs

Features and specifications subject to change without prior notice.

Dynablast®



Distributed by:

LPEXPERT 2013 Inc
1008, rue Marcoux, porte 103
Granby (QC) J2J 2M8
lpexpert@videotron.ca 450 375.3954

www.dynablast.com

BEN/P-B-03/07