

CRDE SERIES

COLD WATER PRESSURE WASHER

Direct Drive • Electric Powered • Industrial Cart

- **Downstream Adjustable Chemical Injector:**
For low pressure soap and chemical injection.
- **Quick Connect Hose Connectors:**
For easy on/off connections and tangle free hoses.
- **Baldor TEFC Motor:**
Low speed induction motor extends the life of your pump.
- **Separate Unloader:**
Diverts water pressure when trigger is not in use. Includes easily adjustable pressure control knob and all brass fittings.
- **Inlet Filter:**
Helps reduce contaminants from entering the pump.
- **Chemical Basket:**
For easy chemical storage.

- **Full Wrap Around Frame for Full Protection:**
With powder-coated finish.



- **10" Never-Go-Flat Tires**
Ball bearing construction with a steel rim and hub assembly.

- **Four Quick Connect Nozzles:**
Colour coded nozzles included are 0°, 15°, 25° and soap.
- **50' High Pressure Hose:**
Durable non-marking steel braided hose.
- **Quality Gun and Stainless Steel Lance Combination:**
Easy pull trigger with 36" lance.
- **High Quality Triplex Plunger Pump:**
All Dynablast pressure washers include GP/Interpump pumps with solid ceramic plungers, thermal pump protector and limited 5 year warranty.
- **Rubber Foot:**
Reduces vibration.

Other Features:

- Warnock Hersey Certified
- Heavy Duty Power Cord and Plug
- Pressure Gauge
- Cart Includes Gun, Lance & Hose Holder



OPTIONAL HOSE REEL AVAILABLE

- DYNAHR150
- DYNA15141718



CR3621DE1
with hose reel

SPECIFICATIONS	ASSEMBLED IN CANADA		
	CR2010DE1	CR3015DE1	CR3621DE1
Operating Pressure (PSI):	1000	1500	2100
Volume (GPM):	2.1	3.0	3.6
Motor (HP):	1.5	3	5
Pump Speed (RPM):	1750	1750	1750
Voltage:	11	230	230
Amps:	13.9	13.2	23
Dimensions - Handle Up (LxWxH):	37" x 26" x 35"	37" x 26" x 35"	37" x 26" x 35"
Unit Weight:	105 lbs	123 lbs	190 lbs

Features and specifications subject to change without prior notice.

Dynablast®



Distributed by:

LPExpert 2013 Inc
1008, rue Marcoux, porte 103
Granby (QC) J2J 2M8
lpexpert@videotron.ca 450 375.3954