

DEF SERIES

HOT WATER PRESSURE WASHER

Direct Drive ♦ Electric Powered ♦ Fuel Oil Heated

- **Downstream Adjustable Chemical Injector -**
For low pressure soap and chemical injection.
- **Quick Connect Hose Connectors -**
For easy on/off connections and tangle free hoses.
- **Large Fuel Tank -**
Holds up to 4.4 gallons of No.1 or No.2 fuel oil. Also includes a fuel indicator gauge.
- **Heavy Duty Steel Frame -**
Includes protective roll cage, hose, holder and a powder coated epoxy finish.
- **Large Burner Temperature Dial -**
Adjust water temperature with ease.
- **Easy Access ON/OFF Toggle Switch -**
Includes indicator light.
- **Replaceable Fuse :**
For electronic overload protection.

- **Stainless Steel Coil Skin -**
Durable rust resistant skin. Schedule 80 coil with 350 000 BTU burner.

Optional Hose Reel - Available for H3025DEF1 and H3030DEF1/3D only. Use P/N HR4KIT.



- **Easy Access Control Panel -**
Makes servicing your machine fast and easy.
- **Four Quick Connect Nozzles -**
Colour coded nozzles included are 0°, 15°, 25° QC.
- **50' High Pressure Hose -**
Durable non-marking steel braided hose.
- **Quality Gun and Lance Combination -**
Easy pull trigger with 48" lance.
- **Separate Unloader -**
Diverts water pressure when trigger is not in use. Includes easily adjustable pressure control knob and brass fittings.
- **High Quality Triplex Plunger Pump -**
All Dynablast pressure washers include GP/Interpump pumps with solid ceramic plungers, thermal pump protector and limited 5 year warranty.
- **13" Pneumatic Tires -**
Ball bearing construction with a steel rim and hub assembly.



Other Features

- **High pressure blow-off valve -** For added safety.
- **Baldor electric ODP motor**
- **Heavy duty power cord**
- **12v Beckett Burner -** No external electricity required.

SPECIFICATIONS

ASSEMBLED IN CANADA

MODEL	H2015DEF1	H3025DEF1	H3030DEF1/3D
Operating Pressure (PSI):	1 500	2 500	3 000
Volume (GPM):	2.0	3.0	3.0
Motor (HP):	2	5	6
Available Voltage (1-phase):	115 V	230 V	230 V
Available Voltage (3-phase):	-	-	575 V
Amps :	20	30	30/7.5
Pump Speed (RPM)	3 450	3 450	1 725
BTU :	172 000	300 000	300 000
Time Delay Shutdown:	No	Yes	Yes
Dimensions - (L x W x H) :	42" x 26" x 40"	42" x 28" x 43"	42" x 28" x 43"
Unit Weight :	290 lb	420 lb	425 lb

Distributed by:

LPExpert 2013 Inc
1008, rue Marcoux, porte 103
Granby (QC) J2J 2M8
lpexpert@videotron.ca 450 375.3954

Dynablast®

